

Versa Lift TM

Auto-Shutter Closure System

Model AS24 Automatic Safety Closure for the Lift Opening

The Auto-Shutter is designed to provide a safety closure for the Versa Lift opening when the lifting platform moves down. This accessory is required whenever the Versa Lift is installed inside the living space of a home, or in a closet, or in an attic space accessible by a passage door from a living space, or on a deck, or any other area where children or pets might have ready access to the lift opening.

The shutter door is lightweight tempered aluminum and is deployed by gravity as the lifting platform frame passes down through the opening. A horizontal support bar is provided to support the door in the raised position. See Fig. 1.

Bracket mounted nylon rollers are provided that mount to the top of the lifting platform frame. These rollers lower the door gradually as the lifting frame descends and raise the door gradually as the lifting frame comes back up. See Fig. 2.

When the lifting platform frame descends below the upper floor, the shutter door is resting on the front and the back of the lift opening. Although the shutter door is not intended to be step surface, it will support up to 200 lbs. See Fig. 3.

The AS24 Auto-Shutter accessory includes all parts and hardware needed for installation, along with illustrated detailed instructions.



Fig. 1: When the lift platform is up, the shutter door rests on a support bar.



Fig. 2: As the lifting platform descends, rollers lower the shutter door.



Fig. 3: When the lift platform is down, the shutter door rests on the floor.

Safe LIFTS

attic storage systems

5001 Spring Valley Rd., Ste. 400E

Dallas, TX 75244

Office: (972) 633-LIFT

Toll-Free: (877) 422-LIFT

Fax: (972) 419-1008

www.SafeLiftsofTexas.com